

UNCLASSIFIED

AD NUMBER
AD029870
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Foreign Government Information; FEB 1954. Other requests shall be referred to British Embassy, 3100 Massachusetts Avenue, NW, Washington, DC 20008.
AUTHORITY
DSTL, AVIA 6/19704, 10 Jul 2008

THIS PAGE IS UNCLASSIFIED

Armed Services Technical Information Agency

Because of our limited supply, you are requested to return this copy WHEN IT HAS SERVED YOUR PURPOSE so that it may be made available to other requesters. Your cooperation will be appreciated.

AD

29870

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by
DOCUMENT SERVICE CENTER
KNOTT BUILDING, DAYTON, 2, OHIO

UNCLASSIFIED

TECH. NOTE
G.W.300

TECH. NOTE
G.W.300

ROYAL AIRCRAFT ESTABLISHMENT
FARNBOROUGH, HANTS

TECHNICAL NOTE: No. G.W.300

**A HIGH SPEED
ELECTRO-MECHANICAL
MULTIPLIER**

by

C.A.A.WASS, B.Sc., A.M.I.E.E.

and D.W.ALLEN

MINISTRY  OF SUPPLY

THIS DOCUMENT IS THE PROPERTY OF H.M. GOVERNMENT AND
ATTENTION IS CALLED TO THE PENALTIES ATTACHING TO
ANY INFRINGEMENT OF THE OFFICIAL SECRETS ACT, 1911-1939

It is intended for the use of the recipient only, and for communication to such officers
under him as may require to be acquainted with its contents in the course of their
duties. The officers exercising this power of communication are responsible that
such information is imparted with due caution and reserve. Any person other than
the authorised holder, upon obtaining possession of this document, by finding or
otherwise, should forward it, together with his name and address, in a closed envelope
to:-

THE SECRETARY, MINISTRY OF SUPPLY, LONDON, W.C.2

Letter postage need not be prepaid, other postage will be refunded. All persons are
hereby warned that the unauthorised retention or destruction of this document is an
offence against the Official Secrets Act

UNCLASSIFIED

U.D.C. No. 621.389 : 518.5 : 511.124

Technical Note No. G.W.300

February, 1954

ROYAL AIRCRAFT ESTABLISHMENT, FARNBOROUGH

A High Speed Electro-Mechanical Multiplier

by

C. A. A. Wass, B.Sc., A.M.I.E.E.,
and
D. W. Allen

SUMMARY

Requirements exist in simulator work for a simple high speed squaring and multiplying unit of moderate accuracy.

This note describes a simple electro-mechanical multiplier using a type E.4 relay as a position servo driving a potentiometer.

The unit will operate on frequencies up to 15 c.p.s. without introducing any appreciable phase shift. Accuracy depends primarily on the quality of the potentiometers used but maximum errors of 1% of the maximum output appear possible.

LIST OF CONTENTS

	<u>Page</u>
1 Introduction	3
2 The Method	3
3 The Multiplier	3
4 Accuracy	3
5 Speed of response	4
6 Conclusions	4
References	5
Advance Distribution	5
Detachable Abstract Cards	-

LIST OF ILLUSTRATIONS

	<u>Fig.</u>
The Multiplying Method	1
The High Speed Electro-Mechanical Multiplier assembled in a "Tridac" brick unit	2
Closed loop response to step input	3
Schematic Diagram of the Multiplier	4
Circuit Diagram of the High Speed Electro-Mechanical Servo	5
Experimental Results for Multiplier	6
Frequency Response of the Amplifier - Relay combination	7a
Frequency Response of the Amplifier - Relay combination	7b
Frequency response of the E.4 Relay driving a piston valve	8
Typical current vs. angle curve for E.4 Relay	9

1 Introduction

In analogue computers of the electronic type it is often required to produce a voltage that is equal to, or proportional to, the product of two given voltages. A number of electronic circuits for multipliers have been devised¹ but these are generally fairly complex or else their accuracy is poor. Electro-mechanical multipliers have also been made but these, usually operated by motors or velodynes, introduce time lags which are too long for many purposes.

It is the purpose of this note to describe an electro-mechanical multiplier which is capable of moderate accuracy and has a time lag of the order of ten milli-seconds only.

2 The Method

It is well known that analogue multiplication can be achieved by the arrangement shown in Fig.1. When V_x is zero the motor turns until the feedback voltage V_f is zero, i.e. until the slider of the potentiometer P_1 is central. When V_x is changed to some other value the motor will turn until $V_f = -V_x$ so that the potentiometer slider will have turned through an angle θ which is proportional to V_x ; i.e. $\theta = k'V_x$, similarly, the slider of potentiometer P_2 will have turned through the same angle θ . Hence, if the ends of the winding of P_2 are at potentials $+V_y$ and $-V_y$, the potential V_o at the slider of P_2 will be proportional to V_y and also to θ . Thus $V_o = k''\theta V_y = k''k'V_xV_y = kV_xV_y$. If both V_y and $-V_y$ are not available a reversing amplifier or alternatively a push-pull amplifier must be used.

3 The Multiplier

The device to be described resembles Fig.1 in principle, but instead of the motor an efficient form of polarised relay² is used. This relay, a rotary type, has a spindle which turns through an angle proportional to the current flowing through the coils over the range of angles $\pm 6^\circ$. An arm attached to the spindle carries two light potentiometer sliders. The two high-grade wire-wound linear potentiometers are supported on an adjustable mount fitted to the base. The general arrangement of one of these devices, mounted in a standard Tridac brick unit is shown in Fig.2.

In order to obtain a suitably damped response such as that shown in Fig.3, some form of damping is required and one possible method, used in the prototype instrument, is the air dash-pot. The one in the illustration was obtained from an aircraft rate-of-turn indicator, but the accuracy is adversely affected by the total friction in the system and it is believed that eddy current damping would be superior.

A schematic diagram of the unit is given in Fig.4 and a circuit diagram of the Relay amplifier in Fig.5.

4 Accuracy

The accuracy of the instrument depends upon the performance of the amplifier-relay-feedback potentiometer servo system and the matching accuracy of the two potentiometers. It is not necessary that the potentiometers be linear but they must be matched. Currently available linear potentiometers of a suitable size³ may be obtained with maximum errors from linearity of the order of 0.1% and therefore matching to 0.2%. The steady state accuracy of the servo system, assuming it is stable, depends

on the torque-current characteristic of the relay, the effective slope of the amplifier and the torque necessary to move the slider arm. The torque-current characteristic of the relay is nearly linear and of the order of 50 gm.cm/ma. and the effective slope of the amplifier is 30 ma./volt. The static friction of the prototype unit was rather high and consequently a torque of 70 gm.cm was necessary to move the slider arm and under these conditions steady state errors of the order of one or two percent would be expected.

At the time when the results given in Fig.6 were obtained high accuracy potentiometers were not available and the potentiometers used were only matched to within about 5%, and this accounts for the large error quoted for the multiplier potentiometer output.

5 Speed of response

The speed of response of the multiplier depends on the torque-inertia ratio of the relay and associated wiper arm. In order to use the full length of a 1" potentiometer a $4\frac{1}{2}$ " wiper arm is needed and its weight should be kept as low as possible while maintaining a high degree of mechanical stiffness. The arm used on the experimental instrument was made of solid bakelised fibre and therefore rather heavy, but even so operating frequencies of 15 cycles per second are possible with negligible phase shift (Fig.7a).

By the use of a properly designed wiper arm and possibly a shorter potentiometer, the maximum operating frequency could be raised considerably and it is of interest to note the frequency response of the E.4 relay driving a piston valve given in Fig.8.

6 Conclusions

It would seem quite possible to construct a multiplier of the type described to have maximum steady state errors of the order of 1% of full scale and a time lag of 10 milliseconds. Such an instrument could also be arranged to produce an output voltage proportional to non-linear functions of the input voltage by the substitution of a suitably shaped or loaded potentiometer for the linear multiplier potentiometer.

REFERENCES

<u>No.</u>	<u>Author</u>	<u>Title, etc.</u>
1	Thomas and Squires	Electronic Analogue Methods of Multiplication. R.A.E. Tech. Note No. G.W.53.
2	Laws	An Electro-Mechanical Transducer with Permanent Magnet Polarisation. R.A.E. Tech. Note No. G.W.202.
3	-	Prov. Spec. for Straight Wirewound Potentiometers. R.A.E. Prov. Spec. No. G.W.72.

Attached: Drgs. GW/P/5010 to 5016
Negs. 110675
Detachable Abstract Cards

Advance Distribution:

Chief Scientist
CGWL
PDSR(GWL)
DG/GW - 95
D Inst RD
DWR(D)
AD/GW (R)
TPA3/TIB - 90

RAE

Director
DD(E)
DD(A)
RPD - 2
Aero
Radio
Arm - 2
Patents
IAP
Instn
Maths Services
GWTW - 2
Library




FIG. 1. THE MULTIPLYING METHOD.

FIG.2. HIGH SPEED ELECTRO-
MECHANICAL MULTIPLIER
ASSEMBLED IN A
"TRIDAC" BRICK UNIT





FIG.3. CLOSED
LOOP RESPONSE
TO STEP INPUT

[step 90% of full pot travel,
time 10 milli-seconds.
(Timing marks as 50 c.p.s.
sine wave peaks)]

FIG.2 & 3.




FIG. 4. SCHEMATIC DIAGRAM OF THE MULTIPLIER.




FIG. 5. CIRCUIT DIAGRAM OF THE HIGH SPEED ELECTRO-MECHANICAL SERVO.




FIG. 6. EXPERIMENTAL RESULTS FOR MULTIPLIER.




FIG. 7B. FREQUENCY RESPONSE OF THE AMPLIFIER-RELAY COMBINATION.




FIG. 8. FREQUENCY RESPONSE OF E.4. RELAY
DRIVING A PISTON VALVE.




FIG. 9. TYPICAL CURRENT vs. ANGLE
CURVE FOR E. 4. RELAY.



*Information Centre
Knowledge Services*
[dstl] Porton Down
Salisbury
Wiltshire
SP4 0JQ
22060-6218
Tel: 01980 613753
Fax 01980 613970

Defense Technical Information Center (DTIC)
8725 John J. Kingman Road, Suit 0944
Fort Belvoir, VA 22060-6218
U.S.A.

AD#: AD029870

Date of Search: 10 July 2008

Record Summary: AVIA 6/19704

Title: High Speed Electro-Mechanical Multiplier
Availability Open Document, Open Description, Normal Closure before FOI Act: 30 years
Former reference (Department) TECH NOTE GW 300
Held by The National Archives, Kew

This document is now available at the National Archives, Kew, Surrey, United Kingdom.

DTIC has checked the National Archives Catalogue website (<http://www.nationalarchives.gov.uk>) and found the document is available and releasable to the public.

Access to UK public records is governed by statute, namely the Public Records Act, 1958, and the Public Records Act, 1967.

The document has been released under the 30 year rule.

(The vast majority of records selected for permanent preservation are made available to the public when they are 30 years old. This is commonly referred to as the 30 year rule and was established by the Public Records Act of 1967).

This document may be treated as UNLIMITED.